

2-Optical 4-Electric POE Gigabit Industrial Switch

FW304GPS-2F

PRODUCT FEATURES

4* 10/100/1000Mbps RJ45 ports+2 * Gigabit SFP ports (uplink)

FW304GPS-2F is a quasi industrial full gigabit management POE switch, which provides 4 gigabit POE ports, 2 gigabit optical ports, full port supports 6KV lightning protection, power supply over temperature protection, over-voltage protection, surge current protection and other protection features. Support IEEE 802.3x full dual and semi dual backpressure flow control. It conforms to IEEE802.3af&at standard, and the maximum PoE power of a single port is 30W. High reliability protection level, adapt to various complex environments, 48-56V DC redundant dual power supply voltage input, support dual redundant DC power supply or dual DC/AC redundant power supply, and meet the power demand in different power supply environments.



PRODUCT DETAILS

Product Model	FW304GPS-2F
---------------	-------------

Network Interface	<ul style="list-style-type: none"> ● 4 10/100/1000M RJ45 ports ● 2 Gigabit SFP ports
Performance Specifications	<ul style="list-style-type: none"> ● MAC address table: 2k ● Backplane bandwidth: 12Gbps ● Packet forwarding rate: 8.9Mpps ● Forwarding mode: store and forward
Power Support	<ul style="list-style-type: none"> ● Maximum output power: 30W ● Voltage input: 48-56V DC ● Input mode: plug-in 5-core 5.08mm spacing terminal block
LED Indicator	<ul style="list-style-type: none"> ● Power indicator: P1, P2 ● Ethernet port indicator: POE&Link&Act1-4 ● Optical port indicator: Link&Act F1-F2
Environmental Specifications	<ul style="list-style-type: none"> ● Operating temperature: - 20-75 °C ● Storage humidity: - 40-85 °C ● Relative humidity: 5% - 95% (non condensing)
Network Protocol	<ul style="list-style-type: none"> ● IEEE802.3、IEEE802.3i、IEEE802.3u、IEEE802.3ab、IEEE802.3z、IEEE802.3af/at
Management	<ul style="list-style-type: none"> ● 2L+
Antistatic	<ul style="list-style-type: none"> ● ±8kV(contact), ±15kV (air)
Size (W*D*H)	<ul style="list-style-type: none"> ● 150*40*127mm

APPLICATION COLLOCATION

